

Pneumatic Stapler Type 71/16-408 K

The BeA 71/16-408 K is special developed for the **furrier**. The low air consumption, long service life and ease of maintenance of this stapler make it a real cost saver.

The stapler is equipped with a comfortable rubber grip and an integrated silencer. The special designed furrier-tool is adjustable in the height. For the furrier application we recommend the staple 71/12 NK DP.



Popular applications:

Furrier

Length:	211 mm
Width:	40 mm
Height:	141 mm

Technical data

Type description:	71/16-408 K Standard
Article code:	12000049
Magazine type :	Bottom loader
Safety:	-
Fastener type:	Type 71
Magazine capacity:	185
Fasteners per strip:	1 x 168
Operating pressure:	5 – 6 bar
Max. operating pressure:	6 bar
Air consumption/operation:	0.3 Liter / 6 bar
Inner hose diameter:	Ø 9 mm LW recommended
Emission sound pressure level at the workstation:	L pA, 1s, d= 82 dB
Single-shot sound pressure level:	L WA, 1 s,d= 87 dB
Weight:	0.83 kg

The vibration as per document no. CEN/TC 255 WG 1 N 47.3 is under the declaration limit as per EN 292-1, amendment A.

Extras supplied with the nailer:

Operating instructions, spare parts list, service instructions, silencer, furrier tool.

Subject to technical modifications.

Accessories:

Article code	Description
14400590	Cap with hanger
14403330	Remote valve compl.
14403535	Mounting flange
14400674	Cap, Alu

All BeA pneumatic tools can be jig-mounted
We supply the necessary accessories and equipments.



This tool conforms to the EG Directive
for Machinery (89/392 EWG)


Pneumatic Stapler Type 71/16-408 K

Staples type 71



BeA Deutschland
Befestigungstechnik
P.O.Box 14 80
D-22904 Ahrensburg
Phone: (04102) 78-0
Fax: (04102) 78-250
www.bea-group.com
e-mail: info@bea-group.com

a division of
Joh. Friedrich Behrens AG



Description	L = Length mm
71/12 NK DP	12

Other lengths and finishes are also available on request.

Explanations:

NK = galvanized steel	BK = bright steel	LM = aluminium	HZ = resin coated
NKS = galvanized steel, extra hard	BKS = bright steel, extra hard	NR = stainless steel, material. 1.4401	DP = divergent point
NKH = galvanized steel, hard	MS = brass	RF = rust resistant, material 1.4301	SA = step cut