



SP-Series For round/small packages



Highlights

■ SPNSC TM/RM

The lightweight tool for mobile and stationary applications

- Weight only 3,2 kg (7 lbs)
- Tensioning force up to 3000 N
- With air connection on top: for strapping applications with suspended hook
- With air connection at rear: for strapping applications without suspension hook

■ SPRM 34

For heavy duty and stationary applications

- Tension force up to 7000 N

■ SPRH 114

For heavy duty and stationary applications

- Tension force up to 8400 N



Strapping tool	SPNSC TM/RM	SPRM 34	SPRH 114
Weight	3,2 kg (7.1 lbs)	7,6 kg (16.8 lbs)	9,3 kg (20.5 lbs)
Tension force	0 – 3000 N	0 – 7000 N	0 – 8400 N
Compressed air consumption (6 bar)			
Tensioning, NI/s	4,0	6,4	6,4
Sealing, NI	3,4	12	14
Seal type	single	double	double
Steel strap			
Width	13, 16, 19 mm (1/2", 5/8", 3/4")	19 mm (3/4")	25, 32 (1", 1 1/4")
Standard quality			
Strap thickness	0,40–0,63 mm (.016" - .025")	0,60–0,80 mm (.023" - .031")	0,80–1,00 mm (.031" - .040")
Tensile strength, up to approx. N/mm ² (lbs/sq.inch)	850 (120 000)	850 (120 000)	850 (120 000)
High tensile quality			
Strap thickness	0,40–0,63 mm (.016" - .025")	0,60–0,80 mm (.023" - .031")	0,60–0,80 mm (.023" - .031")
Tensile strength, up to approx. N/mm ² (lbs/sq.inch)	1100 (157 000)	1100 (157 000)	1100 (157 000)

