

Flejadora neumática para flejar con unión.



MODELO

Código	Tipo	Fleje	Espesor
T511943	OMS 51 19 mm 9000N 3B	R 850 N/mm ² R 1100 N/mm ²	0.6 mm 0.024" 1.1 mm 0.039" 0.63 mm 0.025" 0.9 mm 0.031"
T512543	OMS 51 25 mm 15000N 3B	R 850 N/mm ² R 1100 N/mm ²	0.6 mm 0.024" 1.1 mm 0.039" 0.63 mm 0.025" 0.9 mm 0.031"
T513243	OMS 51 32 mm 15000N 3B	R 850 N/mm ² R 1100 N/mm ²	0.6 mm 0.024" 1.1 mm 0.039" 0.63 mm 0.025" 0.9 mm 0.031"

ESPECIFICACIONES

Dimensiones y peso :

Largo	430 mm 16.9"
Ancho	260 mm 10.2"
Alto	310 mm 12.2"
Peso	11.3 Kg 25 lbs

Alimentación :

Presión de trabajo	5.5 - 7 bar / 78-99 psi
Batería	12 L/s - 25 cuft/min

Prestaciones :

Tensionamiento máximo*	9000 N - 15000 N 6 bar 87 psi
Velocidad de tensionamiento	4,5 m/min @ 9000N 4 m/min @ 15000N
Tipo de cierre	Sellado doble grapa
Resistencia al cierre	80% de la carga de rotura

* variable en función del tipo de fleje

UNIÓN

