

1606R32 TENSOR FLEJE TEXTIL R32 BATERIA 32 MM



POWERFUL & RELIABLE

- > **Tensioning Force** – Max. Tension **800 daN**.
- > **Industrial Grade Tool** – This tensioner is completely designed and newly molded for Industrial Grade use.
- > The CA-SIG 32BT Power is NOT made by simply attaching a typical electric drill to a manual windlass tensioner.

SMART & EASY

- > **Electronic Control Unit (ECU)** – 3 pre-programmed tension modes: Auto/Semi/ Manual. And tension torque (1-6 levels) are electronically controlled (No need to hand turn a manual clutch to change torque).
- > **Designated Quick Reverse Button (QRB)** – preprogrammed auto reverse button allows for easy reverse turning of the windlass for quick tool removal after tension (without having to switch back and forth on the Forward/Reverse button on a typical electric drill).
- > **Cutter** – designed to cut Composite cord straps.

SPECIFICATION

- > Strap type: Composite & Woven cord strapping
- > Strap width: 19 - 32mm; Thickness: 0.85~1.65mm
- > Tensioning force: 6 settings (300 - 800 daN)
- > Tensioning speed: 35 mm/s
- > Weight including battery: approx. 3.6 kg

SAFETY

- > Single-handed operation **conforms to CE safety directive** and meets RoHS requirements.
- > Li-Ion battery **complies with UN38.3** safety requirements.

LATEST TECHNOLOGY

- > **Brushless Motor** – This 4th generation Brushless Motor generates a very steady output to ensure consistent and reliable tensioning for your cord strapping needs.
- > **Bosch 18V 4.0Ah Li-Ion Battery** – rechargeable battery with Charge Level Indicator (CLI), can strap up to 350 cycles per fully charged battery.

ERGONOMIC

- > **6 Degree Angle on the handle bar** – ergonomically designed to lessen wrist fatigue while tensioning on a flat surface, and during vertical operation.
- > **Low Center of Gravity design** – reduced the overall height of the tensioner to lessen operating fatigue during horizontal & vertical operation.



Ergonomically designed to lessen wrist fatigue