

nuova MICRA



MICRA M

CONFEZIONATRICE ANGOLARE A CAMPANA

CARATTERISTICHE MACCHINA

Dimensioni saldatore	540x390 mm
Discesa manuale della barra saldatrice con dispositivo di ritorno automatico	STD
Saldatura ad impulso con regolazione automatica del tempo di saldatura	STD
Altezza di lavoro (con gambe)	920 mm
Contapezzi	STD
Scheda con 10 programmi	STD
Tensione di alimentazione	230 V. 1 Ph - 50/60 Hz
Potenza installata	3,15 KW

CARATTERISTICHE BOBINA FILM

Diametro esterno max (D)	250 mm
Altezza bobina film (H)	600 mm
Diametro interno (D)	76 mm

new Micra



MICRA M

SEAL & SHRINK PACKAGING MACHINES

MACHINE CHARACTERISTICS

Sealing frame dimensions	540x390 mm
Manually operated sealing bar with automatic return	STD
Impulse sealing system with automatic sealing time adjustment	STD
Max working height (with legs)	920 mm
Counting Device	STD
Electronic board with 10 programs	STD
Power supply voltage	230 V. 1 Ph - 50/60 Hz
Installed power	3,15 KW

FILM SPOOL CHARACTERISTICS

Max. external diameter (D)	250 mm
Film spool height (H)	600 mm
Internal diameter (D)	76 mm