

# nuova MICRA



## MICRA L

CONFEZIONATRICE ANGOLARE A CAMPANA

### CARATTERISTICHE MACCHINA

Dimensioni saldatore	840x590 mm
Discesa manuale della barra saldante con dispositivo di ritorno automatico	STD
Saldatura ad impulso con regolazione automatica del tempo di saldatura	STD
Altezza di lavoro	950 mm
Contapezzi	STD
Scheda con 10 programmi	STD
Tensione di alimentazione	400 V. 1 Ph - 50/60 Hz
Potenza installata	5,3 KW

### CARATTERISTICHE BOBINA FILM

Diametro esterno max (D)	300 mm
Altezza bobina film (H)	800 mm
Diametro interno (D)	76 mm

# nuova Micra



## MICRA L

SEAL & SHRINK PACKAGING MACHINES

### MACHINE CHARACTERISTICS

Sealing frame dimensions	840x590 mm
Manually operated sealing bar with automatic return	STD
Impulse sealing system with automatic sealing time adjustment	STD
Max working height (with legs)	950 mm
Counting Device	STD
Electronic board with 10 programs	STD
Power supply voltage	400 V. 1 Ph - 50/60 Hz
Installed power	5,3 KW

### FILM SPOOL CHARACTERISTICS

Max. external diameter (D)	300 mm
Film spool height (H)	800 mm
Internal diameter (D)	76 mm