

Highly efficient, secure banding of a wide variety of works.

■ FEATURES

- Banding can be several times more efficient than that of hand taping.
- Patented mechanism for smooth tape feeding and taping.
- Heat adhesion system ensures very tight banding.
- Items to be taped are free from any stain as no subsidiary materials (adhesives, hot melt etc.) are used.
- Single winding design features tape cost saving.

Desk-top design features space saving and light weight for easy setting at any

place.



10		
	0	
1	COM	
	A STATE OF THE PARTY OF THE PAR	JD-24

■ CAPABILITY

Model	Product size	Speed
JD-150F	Max. (width 150mm, height 140mm) Min. (width 30mm, height 5mm)	25 cycles/minute
JD-240	Max. (width 240mm, height 170mm) Min. (width 30mm, height 5mm)	(approx.)

■ MACHINE SPECIFICATIONS

Model	Tape width (mm)	Width	Height	Depth	Table height	Power supply	Allowable tape
	0-150F-20/30 -240-20/25/30	425mm	400mm	287mm	- 230mm	115V/220V/230V/240V 50Hz/60Hz	Film tapes Paper tapes
J	ID-150F-40	435mm		300mm			Film tapes
	JD-240-40	400111111					Paper tapes

■ COM TAPE SPECIFICATIONS

Туре	Width	Thickness		
Paper	20mm/25mm/30mm/40mm	70g (brown)/80g (white)		
Film	20mm/30mm/40mm	80 micron/100 micron/MAGIC CUT 110 micron		

Note: Use only the tapes supplied or approved by the machine manufacturer.

COM is Communication.



ROZA-GRAPINSA

Other than tapes mentioned above; color tapes, printed tapes, etc., can also be made to order.

[•] Specifications subject to change without notice.