

6-Lobe Pin Self Drilling Screws

Self drilling screws manufactured in a 6-Lobe Pin security drive (sometimes known as Star Drive Pin, Pin Torx or Resistorx®). Self drilling tips provide fast and easy application eliminating the need to pre-drill.

Requires matching tooling *See page 47*



INSERT BITS

Manufactured in case hardened Delta Protekt® plated steel.

Self Drilling Screws

COUNTERSUNK ■ DELTA PROTEKT® PLATED BOX QTY 100



GAUGE	LENGTH	1/2"	3/4"	1"	1 1/2"	2"	DRIVER SIZE
		13mm	19mm	25mm	38mm	50mm	
8	4.2mm	RTCD08D -DP	RTCD08F -DP	RTCD08G -DP	RTCD08I -DP		T20
10	4.8mm		RTCD10F -DP	RTCD10G -DP	RTCD10I -DP	RTCD10J -DP	T25
12	5.5mm			RTCD12G -DP	RTCD12I -DP	RTCD12J -DP	T27



PAN HEAD ■ DELTA PROTEKT® PLATED BOX QTY 100



GAUGE	LENGTH	1/2"	3/4"	1"	1 1/2"	2"	DRIVER SIZE
		13mm	19mm	25mm	38mm	50mm	
8	4.2mm	RTPD08D -DP	RTPD08F -DP	RTPD08G -DP	RTPD08I -DP		T20
10	4.8mm		RTPD10F -DP	RTPD10G -DP	RTPD10I -DP	RTPD10J -DP	T25
12	5.5mm			RTPD12G -DP	RTPD12I -DP	RTPD12J -DP	T27



SELF DRILLING SCREWS TECHNICAL INFO (mm)

HEAD STYLE	GAUGE	No. 8	No. 10	No. 12
		4.2mm	4.8mm	5.5mm
COUNTERSUNK HEAD		7.9	9.3	10.6
		3.0	3.2	3.7
PAN HEAD		7.9	9.3	10.6
		2.9	3.4	3.9
POINT SIZE		2	3	3
MATERIAL THICKNESS Mild Steel up to (mm)		1 + 2	2 + 2	2 + 3

All sizes shown are without min and max tolerances and are guide sizes.