



# C-690 Labeljet

Outstanding Inkjet printer for  
Time-saving and Easy-to-use

Simple, fast and economical color label printer.

With state-of-art technology to achieve precise and high quality printing.  
Ideal for a variety of labels and diverse applications.



individual CMYK ink cartridges to fulfill full-color printing



Standard with Ethernet, USB port and roll unwinder



one touch of the button and done




Free GoLabel PDF design software for handling various combinations

# Product Specifications

## C-690LJ Inkjet Printer

Barcodes Made Easy

Model		C – 690LJ	
<b>Print Technology</b>	Drop-on-demand thermal inkjet		
<b>Print Quality</b>	Black: up to 1200 dpi rendered black text Color: up to 1200 x 1200 dpi		
<b>Print Speed</b>	Up to 6 Inch/Second (300 dpi)		
<b>Print cartridge capacity</b>	Black: 69 ml (dye Ink), 66ml (pigment Ink), Color (CMY): 28 ml,		
<b>Compatible Operating Systems</b>	Windows® XP, Vista, 7 (32 and 64 bit)		
<b>Paper Sensors</b>	Adjustable GAP, Black Mark sensor from 0 to 3.2" Adjustable BlackMark on top (BMT)		
<b>Media Dimensions</b>		<b>Max</b>	<b>Min</b>
	Label width	203 mm (8")	38 mm (1.5")
	Media width	216 mm (8.5")	38 mm (1.5")
	Label height	500 mm (19.7")	40 mm (1.6")
	Gap	5 mm (0.02")	2 mm (0.08")
			
<b>Media Feed</b>	Sensor supervised label feed Single paper sheets (manual)		
<b>Media Types</b>	Rolls of labels and tags, fanfold paper and single paper sheets		
<b>Label Rolls</b>	Maximum label/tag roll diameter 9" Maximum roll width 8.5"		
<b>Label Detection</b>	Fanfold, Gap, Black Mark		
<b>Interfaces</b>	Built-in wired ethernet USB 2.0 (Plug & Play (Windows Driver))		
<b>Page Description Language</b>	PCL3e		
<b>Power Requirements</b>	External power supply: 100 - 240 VAC (+/-10%), 50/60 Hz (+/-2Hz)		
<b>Power Consumption (maximum)</b>	28 W when printing 6 W when idle^ 0.6 W (220V) when off 0.4 W (110V) when off		
<b>Dimensions</b>	<b>Width</b>	500 mm	
	<b>Height</b>	400 mm	
	<b>Depth</b>	250 mm	
<b>Weight</b>	20 Kg		
<b>Warranty</b>	12 Months warranty (bring-in) warranty extensions optional		
<b>Agency approvals</b>	CE		
<b>Options</b>	Rewinder Cutter		

\* Specifications are subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective owners.

\*\* Minimum print height and maximum print speed specification compliance can be dependent on non-standard material variables such as label type, thickness, spacing, liner construction, etc. Godex is pleased to test non-standard materials for minimum print height and maximum print speed capability.

Re 2.3 2013/8/1