



Fastener type

BeA Countersunk nails SKDA 600, KMR Brads DA
 · Diameter: 1,8 mm

Product strengths

- Adjustable depth setting
- Li-ion battery
- Rubberized safety yoke

Scope of operation

Carpentry, Dry and interior extension, Joinery, Measurement and assembly construction, Roofing and facade, Terrace, path

Scope of delivery

Battery charger, Li-Ion Battery, Transport case, User manual


More details:



Technical data

EAN	4045758121146
Type of fastener	BeA Countersunk nails SKDA 600, KMR Brads DA
Fastener diameter min	1,8 mm
Fastener diameter max	1,8 mm
Fastener length min	32 mm
Fastener length max	64 mm
Weight	2,12 kg
Driving system	Battery and combustion chamber
Activation method	Single activation
Tool length	350 mm
Tool width	153 mm
Tool height	305 mm
Battery type	Li-ion
Impacts (for fuel cell)	1200
Hits per battery charge	4000
Declaration of conformity	CE, EAC, UKCA
Noise characteristic L pA, 1s according to EN 12549	89,4 dB(A)
Noise characteristic L WA, 1s, d according to EN 12549	96,8 dB(A)
Noise characteristic K pA and K WA according to EN 12549	2,5 dB(A)
Vibration value ahd according to ISO 8662	1,93 m/s ²
Weight incl. packaging	6,2 kg

Related fastener




BeA Countersunk nails SKDA 600

- Diameter: 1,8 mm
- Length: 32 - 63 mm

Item No.	Diameter x Length	Nail shank	Material
10300397	1,8 mm x 32 mm	Smooth shank	Steel, galvanized
10300398	1,8 mm x 38 mm	Smooth shank	Steel, galvanized
10300399	1,8 mm x 44 mm	Smooth shank	Steel, galvanized
10300400	1,8 mm x 50 mm	Smooth shank	Steel, galvanized
10300401	1,8 mm x 56 mm	Smooth shank	Steel, galvanized
10300402	1,8 mm x 63 mm	Smooth shank	Steel, galvanized
10300405	1,8 mm x 38 mm	Smooth shank	Stainless Steel (AISI 304, EN grade 1.4301, A2)
10300407	1,8 mm x 50 mm	Smooth shank	Stainless Steel (AISI 304, EN grade 1.4301, A2)
10300409	1,8 mm x 63 mm	Smooth shank	Stainless Steel (AISI 304, EN grade 1.4301, A2)

Related fastener



KMR Brads DA

- Diameter: 1,8 mm
- Length: 32 - 64 mm

Item No.	Length	Point type	Material
10300761	1,8 mm x 32 mm	Chisel point	Steel, galvanized
10300762	1,8 mm x 38 mm	Chisel point	Stainless Steel (AISI 304, EN grade 1.4301, A2)
10300764	1,8 mm x 44 mm	Chisel point	Steel, galvanized
10300765	1,8 mm x 50 mm	Chisel point	Stainless Steel (AISI 304, EN grade 1.4301, A2)
10300766	1,8 mm x 50 mm	Chisel point	Steel, galvanized
10300767	1,8 mm x 56 mm	Chisel point	Stainless Steel (AISI 304, EN grade 1.4301, A2)
10300768	1,8 mm x 56 mm	Chisel point	Steel, galvanized
10300769	1,8 mm x 64 mm	Chisel point	Stainless Steel (AISI 304, EN grade 1.4301, A2)
10300770	1,8 mm x 64 mm	Chisel point	Steel, galvanized
10300907	1,8 mm x 32 mm	Chisel point	Steel, galvanized
10300908	1,8 mm x 38 mm	Chisel point	Steel, galvanized
10300909	1,8 mm x 44 mm	Chisel point	Steel, galvanized
10300910	1,8 mm x 50 mm	Chisel point	Steel, galvanized

Other variations and sizes on request